



700 SERIES

FR 2632 AT AIR



*Overseas model pictured.
May contain items not standard to the NZ model.

Euro 6
Emissions Standard
6 x 2 Cab Chassis

KEY FEATURES

- | | |
|--|--|
| ✓ Engine Retarder Brake (Jake Brake) | ✓ Euro 6 Emissions Standard |
| ✓ ISRI NTSC2 Driver's Seat with integrated safety belt | ✓ Hino SmartSafe incl. PCS, VSC, ABS, EBS, ASR, LDWS, & Driver Monitor |
| ✓ Differential Cross Lock | ✓ Adaptive Cruise Control |
| ✓ LED Main Beam Headlamps with DRLs | ✓ Reverse Camera & Buzzer |
| ✓ ECE-R29 Cab Strength Certified | ✓ Polished Aloca Alloy Wheels |


KEY SPECIFICATIONS

GVM	26,000 or 18,000kg
GCM	36,500kg
Power	320hp / 235kW
Torque	1,275Nm
Transmission	6 Speed Automatic
Wheelbase	6.38m

ENGINE

Model	HINO A09C-VP
Max. Output (ISO NET)	320hp / 235kW @ 1,800 RPM
Max. Torque (ISO NET)	1,275Nm @ 1,100-1,600 RPM
Max. Engine RPM	2,100 RPM
Engine Compliance	Euro 6
Type	Diesel, turbocharged & intercooled, 6 cylinder inline, 4 cycle, overhead camshaft, watercooled
Combustion System	Direct injection
Bore & Stroke	112 x 150mm
Piston Displacement	8.866L
Compression Ratio	17.0:1
Fuel Injection	Electronic control common rail
Air Compressor / Bore & Stroke	Single cylinder bore & stroke, 95 x 60mm
Air Cleaner	Behind cab mounted paper elements
Exhaust	Horizontal outlet
Emission Control System	DPR, EGR, & SCR (AdBlue®)
Engine Immobiliser	Equipped

POWER & TORQUE CHART (ISO NET) A09C-VP



PERFORMANCE

Calculations based on 26,000kg GVM with 11R22.5 tyres

Engine RPM @ 100km/h	1,788
Road Speed Limited to (km/h)	100
Max. Theoretical Speed (km/h)	117
Gradeability Tan (%) @ GVM	29.4

TRANSMISSION & GEAR RATIOS

Make & Description	Allison 3200 Automatic	
Type	6 Speed Automatic with Overdrive	
Gear Ratios	1	3.487
	2	1.864
	3	1.409
	4	1.000
	5	0.750
	6	0.653
	Reverse	5.027
Torque Converter Ratio	1.77:1	
Final Drive Ratio	5.250:1	

BRAKES

Type	Full air, taper roller, leading & trailing shoes (drum)	
Control	Dual circuit	
Drum Diameter x Lining Width	Front	406.4 x 152mm
	Rear	406.4 x 216mm
Air Dryer	Equipped	
Auto Brake Shoe Adjuster	Equipped	
Electronic Brake System (EBS)	Equipped	
Anti-Lock Brake System (ABS)	Equipped	
Anti-Slip Regulation (ASR)	Equipped	
Engine Brake (Jake Brake)	Equipped	
Exhaust Brake	Equipped	
Brake Sync	Brake pedal activated engine brake	

FUEL TANK & SUPPLY

Material	Alloy
Fuel Capacity	390L
Lockable Fuel Cap	Equipped
Prefilter & Sedimenter	Equipped
AdBlue® Capacity	28L

STEERING

Type	Telescopic tilt steering column, recirculating ball, integral power steering	
Steering Angle	Inner - 49°	Outer - 34°

ELECTRICAL

Type	24V negative earth
Batteries	2 x 12V 120Ah 115F51
Alternator Capacity	24V x 90A
Starter Type	24V x 6.0kW
Auto On/Off Headlamps	LED
Daytime Running Lamps (DRLs)	LED
Cornering Lamps	Equipped

SAFETY FEATURES

Active Safety Features - HINO SmartSafe

Vehicle Stability Control (VSC)	Equipped
Anti-Lock Brake System (ABS)	Equipped
Electronic Control Braking System (EBS)	Equipped
Pre-Collision System (PCS)	Equipped
PCS is inclusive of	Safety Eye (SE) Autonomous Emergency Braking (AEB) Pedestrian Detection (PD)
Driver Monitor (DM)	Equipped
Lane Departure Warning System (LDWS)	Equipped
Anti-Slip Regulation (ASR)	Equipped
Auto Brake Shoe Adjuster	Equipped
Engine Retarder (Jake Brake)	Equipped
Adaptive Cruise Control (ACC)	Equipped
Reverse Buzzer & Camera (RC)	Equipped

Passive Safety Features

SRS Airbag	Equipped (for driver)
SRS Seat Belt Pretensioner	Equipped (for driver)
Front Underrun Protection Device (FUPD)	Equipped
ECE-R29 Cab Strength Certified	Equipped

AXLE, SUSPENSION & LOAD LIMITS

Front	Front Axle Model	MF781R
	Front Axle Type	Reversed Elliot I Section Beam
	Front Suspension Type	Taper leaf springs with stabiliser
	Axle Limit (incl. Suspension)	7,500kg
Rear	Rear Axle Model	SH17 with Tag Lazy axle
	Differential Cross Lock	Equipped
	Rear Axle Type	Fully floating, single reduction by hypoid gears, with differential cross lock
	Rear Suspension Type	Hendrickson HAS with ECAS & Road Friendly Suspension Certified
	Axle Limit (incl. Suspension)	20,000kg

WHEELS & TYRES

Wheel Type	Alcoa Alloy 10-stud (ISO 335 PCD)
Rim Size	22.5 x 8.25 (wide single 22.5 x 11.75 optional)
Tyre Size	275/70R22.5 152/148 (11R22.5 optional)
Number of Tyres	11 (incl. spare)

CHASSIS FRAME



Main Section (depth x flange x thickness)	302 x 80 x 9.0mm
Chassis Width	840mm
Tensile Strength	620 N/mm ² (63 kgf/mm ²)
Tow Hook (Front & Rear)	Equipped
Type	Ladder-shaped channel section side rails

CAB DETAILS

Type	Forward control, all steel, welded construction, fully floating air suspended with electro-hydraulic power tilt
Grille Colour	Chrome
Seating Capacity	2
Driver's Seat	ISRI 6860/870 NTSC2, 7-way adjustable
Side Passenger Seat	High-back, reclining seat with fabric cover
Seat Belts	Driver: 3-point pretensioner Passenger: 3-point type
Sunvisor & Overhead Console	Equipped
Windscreen Wipers	Triple arm wiper with intermittent & variable controls
Windscreen Glass	Heat-absorbing laminated glass
Cab Heater & Air Conditioner	Equipped
Auxiliary Power Supply	12V x 120W socket and USB 2.1A
External Rear-View Mirrors	2 flat type, electric and heated
	2 convex spotters and blind spotters
	LHS and front kerb view mirrors
Central Locking & Keyless Entry	Equipped
Cab Storage Pockets	Equipped
Power Windows	Equipped
Foot Rest	Equipped
Cup Holders	Centre tray and door pockets
Multimedia System	Kenwood DMX7022S, 6.8" WVGA touch screen display with 13-band EQ, Bluetooth®, Apple CarPlay & Android Auto™ via USB, 3 preouts 5.0V

INSTRUMENTATION

LCD Display	Meters & Gauges
✓ Date, Day, & Time	✓ Speedometer
✓ Temperature Gauge	✓ Tachometer
✓ Fuel & AdBlue® Gauges	✓ Air Gauges
Additional Switches & Controls	
✓ Odometer & Hour Meter	✓ VSC, PCS, & LDWS Off
✓ Battery Warning	✓ Air Con Controls
Multi Information Display (MID)	✓ Differential Cross Lock
✓ General Information	✓ Brake Sync
✓ Safety Feature Settings	✓ Shift Selector
✓ Cruise Control	✓ Idle Up
✓ Eco Tree	✓ Quick Warm Up
✓ Display Settings	✓ DPR Regeneration
✓ System Check	✓ ECO Run
Steering Wheel & Column Controls	✓ Powered Mirror Control
✓ Cruise Control	✓ Mirror Heater
✓ MID Controls	✓ Electronic Window Lock Out
✓ Headlights, Indicators, Window Wipers	✓ Headlight Leveller
✓ Engine Braking Control	✓ Hazard Lights
✓ Handsfree Phone	



Drawings are for reference only to the table. For specific chassis layouts and dimensions, please refer to Body Mounting Manual drawings.

DIMENSIONS (MM)

Model	FR1AWKH-DXCPEAC
Product Code	FR 2632 AT AIR 6375
Suspension	Air
Wheelbase (WB)	6,375
Overall Length (OL)	11,200
Overall Width (OW)	2,490
Overall Height (OH)	2,815
Cab to Axle Centre (CA)	5,715
Front Overhang (FOH)	1,400
Rear Overhang (ROH)	3,412
Front Chassis Height (FCH)	975
Rear Chassis Height (RCH)	995
Front Track (FT)	2,050
Rear Track (RT)	1,835
Road Clearance (RC)	245
Kerb to Kerb	22,400
Wall to Wall	24,200
Indicative Chassis Mass (kg) – with 10L of fuel, tools, spare tyre, and subject to a ±3% tolerance	
Total	7,381
Front	4,195
Rear	3,186
GVM	26,000 or 18,000
GCM	36,500

WARRANTY (PLEASE REFER TO HDL WARRANTY CONDITIONS)

Standard Warranty

Engine & Powerlines

36 months or 250,000kms
(whichever comes first)

DISCLAIMER

Hino Trucks are distributed in New Zealand by Hino Distributors (NZ) Ltd.

All efforts have been made to ensure the information contained in this brochure was correct at time of printing or uploading. Hino Distributors (NZ) Ltd reserves the right to alter any details of the specifications and equipment without notice. Hino in so far as it is permitted by law to do so, shall not be liable in any way as a result of any reliance placed by any person on anything contained in this brochure. You should therefore check with your authorised Hino dealer at the time of ordering your motor vehicle to ensure that colour, specifications, equipment, design features and options are available for the vehicle you are ordering. Please note that some options may only be available in combination with others. Authorised Hino dealers will on request provide up to date information on all accessories, design features, prices and availability.